(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 31 December 2003 (31.12.2003)

(10) International Publication Number WO 2004/001475 A1

(51) International Patent Classification7:

G02B 6/42

(21) International Application Number:

PCT/F12003/000508

(22) International Filing Date:

23 June 2003 (23.06.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

20021225

24 June 2002 (24.06.2002)

- (71) Applicant (for all designated States except US): NOKIA OYJ [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): KAUTIO, Kari [FVFI]; Tiukutie 16, FIN-90250 Oulu (FI). KOPOLA, Harri [FVFI]; Karjakentäntie 20, FIN-90540 Oulu (FI).
- (74) Agent: HEINÄNEN OY; Annankatu 31-33 C, FIN-00100 Helsinki (FI).

(81) Designated States (national): AE, AG, AL, AM, AT, AU. AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD. SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, 2A, ZM, 2W.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW). Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4-17:


of inventorship (Rule 4.17(iv)) for US only

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ALIGNMENT OF AN OPTIC OR ELECTRONIC COMPONENT



(57) Abstract: A method and an arrangement for aligning at least one optic and/or electronic component (2) on a substrate (3) or a corresponding support structure, wherein the method comprises: arranging a hole (4) in the support structure; arranging at least three stud bumps (5) on the surface of the component (2); and arranging said stud bumps along the periphery of the hole (4) for alignment of the component (2) to the hole (4).